



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

| | |
|--------|---|
| Series | Algae growth chambers LED Lighting Temperature and Humidity |
| Model | agc-rh-170 |

170 litre LED algae growth chamber
Temperature and humidity control



*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Algae growth chambers
 LED Lighting
 Temperature and Humidity
Model agc-rh-170

170 litre LED algae growth chamber
Temperature and humidity control

| | |
|-----------------------|-----------------------------------|
| Chamber capacity | 170 Litres |
| Chamber width | 700 mm |
| Chamber depth | 600 mm |
| Chamber height | 405 mm |
| Chamber material | Stainless Steel 304L |
| External width | 866 mm |
| External depth | 784 mm |
| External height | 1085 mm |
| External material | Durable epoxy powder-coated steel |
| Recommended clearance | 75mm on sides and rear |
| Temperature range | 4 to 50C |
| Temperature sensor | Pt100 |
| Control accuracy | 0.1 C |
| Temporal stability | 0.2 C |
| Shelves supplied | 1 |
| Shelf dimensions | 690 x 590 mm |
| Shelf spacing | 84 mm |
| Shelf capacity | 50 KG |
| Insulation type | Mineral Wool - asbestos free |
| Insulation thickness | 50mm |
| Compressor size | 1/3 HP |
| Refrigerant | CFC-Free R134a |




Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Algae growth chambers
LED Lighting
Temperature and Humidity
Model agc-rh-170

170 litre LED algae growth chamber
Temperature and humidity control

| | |
|-------------------|--|
| Lighting source | Bi-Directional (up/down) Waterproof LED Cassettes Lighting directly above and below entire shelf |
| Growth area | 0.4m ² (per shelf) |
| Maximum intensity | 200μmol/m ² /sec |
| Lighting colours | Lighting cassettes comprised of any combination of: Warm White Cool White Red Green Blue RGB Combination—Variable spectrum |



| | |
|----------------------|---|
| Electrical supply | Single phase, 220 - 240V, 50 - 60 Hz (alternatives available on request) |
| Element rating | 0.75 kW |
| Circulating fan | 1 |
| Controller type | Multifunction intelligent digital PID-microprocessor |
| Readout | Digital LCD readout of set and actual temperature |
| Temperature alarms | High low deviation |
| Programmable Control | 500 step programmable control of temperature, humidity and lighting |
| Country of origin | Australia |




Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Algae growth chambers
 LED Lighting
 Temperature and Humidity
Model agc-rh-170

170 litre LED algae growth chamber
Temperature and humidity control

| | |
|--------------------|-------------|
| Humidity Range | 20 - 90% RH |
| Humidity sensor | |
| Control accuracy | 0.1 % |
| Temporal stability | 0.5 % |



If the temperature setpoint is below 20 C, the RH control will be disabled and the chamber will adopt a natural value depending on the internal chamber conditions

This graph is a guide only
Variations to the envelope can occur due to ambient conditions,
the intensity of internal lighting, heat loads or humidity loads,
and the nature of the product placed within the chamber.



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

| | |
|--------|---|
| Series | Algae growth chambers LED Lighting Temperature and Humidity |
| Model | agc-rh-170 |

170 litre LED algae growth chamber
Temperature and humidity control

Options / Accessories

- Additional shelves
- Inner viewing door - toughened glass
- Double glazed glass door
- Side access port - 50 mm
- Fan speed controller
- Internal power supply*
- Inner viewing light - LED*
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Co2 Control (ambient to 3000ppm)

*Maximum temperature limited to 50C