



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Medical Drying Cabinet
Model dmi-500

500 litre medical drying cabinet
Instruments only



*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Medical Drying Cabinet
Model dmi-500

500 litre medical drying cabinet
Instruments only

Chamber capacity	500 Litres
Chamber width	700 mm
Chamber depth	600 mm
Chamber height	1136 mm
Chamber material	Stainless Steel 304L
External width	866 mm
External depth	784 mm
External height	1815 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	(Ambient + 7C) to 150C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Available shelf positions	12
Shelves supplied	3
Shelf dimensions	690 x 590 mm
Shelf spacing	89mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm
Circulating fan	1
Airflow System	Moisture extraction system for high performance drying of moisture laden content utilizing. Fresh dry air intake—Hot moist air extraction
Exhaust diameter (mm)	63 - top mounted



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Medical Drying Cabinet
Model dmi-500

500 litre medical drying cabinet
Instruments only

Countdown timer	99 hr 59 min - or continuous
Controller type	Multifunction intelligent digital PID-microprocessor
Readout	Digital LCD readout of set and actual temperature
Temperature alarms	High low deviation
Country of origin	Australia

Options / Accessories

- Additional shelves
- 8 Step programmable controller
- 500 Step programmable controller
- Side access port - 50 mm
- Fan speed controller
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Swivel castors - Front lockable
- Modulating Valve (Baffles fresh air intake). Increased maximum temperature to 200C