



STERID IUM

Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Soil Drying Ovens
Model ds-810

810 litre soil drying oven





Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Soil Drying Ovens
Model ds-810

810 litre soil drying oven

AS1289 - 2000	Compliant
AS1141 - 1999	Compliant
Average evaporation rate	35g/hour
Chamber capacity	810 Litres
Chamber width	842 mm
Chamber depth	705 mm
Chamber height	1372 mm
Chamber material	Stainless Steel 304L
External width	1048 mm
External depth	840 mm
External height	1982 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	(Ambient + 7C) to 150C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Available shelf positions	16
Shelves supplied	3
Shelf dimensions	836 x 700 mm
Shelf spacing	77mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm
Circulating fan	1
Airflow System	Moisture extraction system for high performance drying of moisture laden content utilizing. Fresh dry air intake—Hot moist air extraction
Exhaust diameter (mm)	63 - top mounted



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Soil Drying Ovens
Model ds-810

810 litre soil drying oven

Countdown timer	99 hr 59 min - or continuous
Controller type	Multifunction intelligent digital PID-microprocessor
Readout	Digital LCD readout of set and actual temperature
Temperature alarms	High low deviation
Country of origin	Australia

Options / Accessories

- Additional shelves
- 8 Step programmable controller
- 500 Step programmable controller
- Side access port - 50 mm
- Fan speed controller
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Swivel castors - Front lockable
- Modulating Valve (Baffles fresh air intake). Increased maximum temperature to 200C