



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature Only
Model er-170

170 litre environmental chamber
temperature only



*Optional double glazed door shown

*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature Only
Model er-170

170 litre environmental chamber
temperature only

Chamber capacity	170 Litres
Chamber width	700 mm
Chamber depth	600 mm
Chamber height	405 mm
Chamber material	Stainless Steel 304L
External width	866 mm
External depth	784 mm
External height	1085 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	4 to 80C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Available shelf positions	4
Shelves supplied	2
Shelf dimensions	690 x 590 mm
Shelf spacing	84 mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm
Compressor size	1/3 HP
Refrigerant	CFC-Free R134a



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature Only
Model er-170

170 litre environmental chamber
temperature only

Electrical supply	Single phase, 220 - 240V, 50 - 60 Hz (alternatives available on request)
Element rating	0.75 kW
Circulating fan	1
Countdown timer	99 hr 59 min - or continuous
Controller type	Multifunction intelligent digital PID-microprocessor
Readout	Digital LCD readout of set and actual temperature
Temperature alarms	High low deviation
Programmable control	8 Step
Country of origin	Australia

Options / Accessories

- Additional shelves
- 500 Step programmable controller
- Inner viewing door - toughened glass
- Double glazed glass door
- Side access port - 50 mm
- Fan speed controller
- Internal power supply*
- Inner viewing light - LED*
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate

*Maximum temperature limited to 50C