



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature and Humidity
Model erf-rh-500

500 litre environmental chamber
temperature and humidity control



*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature and Humidity
Model erf-rh-500

500 litre environmental chamber
temperature and humidity control

Chamber capacity	500 Litres
Chamber width	700 mm
Chamber depth	600 mm
Chamber height	1136 mm
Chamber material	Stainless Steel 304L
External width	866 mm
External depth	784 mm
External height	1815 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	-20 to 80C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Available shelf positions	12
Shelves supplied	3
Shelf dimensions	690 x 590 mm
Shelf spacing	89 mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm




Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature and Humidity
Model erf-rh-500

500 litre environmental chamber
temperature and humidity control

Humidity Range	20 - 90% RH
Humidity sensor	
Control accuracy	0.1 %
Temporal stability	0.5 %



If the temperature setpoint is below 20 or above 80C, the RH control will be disabled and the chamber will adopt a natural value depending on the internal chamber conditions

This graph is a guide only
Variations to the envelope can occur due to ambient conditions,
the intensity of internal lighting, heat loads or humidity loads,
and the nature of the product placed within the chamber.



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Environmental Chambers
Temperature and Humidity
Model erf-rh-500

500 litre environmental chamber
temperature and humidity control

Electrical supply	Single phase, 220 - 240V, 50 Hz (alternatives available on request)
Element rating	1 kW
Circulating fan	1
Countdown timer	99 hr 59 min - or continuous
Controller type	Multifunction intelligent digital PID-microprocessor
Readout	Digital LCD readout of set and actual temperature
Temperature alarms	High low deviation
Programmable control	500 step programmable control of temp & humidity
Country of origin	Australia

Options / Accessories

- Additional shelves
- Inner viewing door - toughened glass
- Double glazed glass door
- Side access port - 50 mm
- Fan speed controller
- Internal power supply*
- Inner viewing light - LED*
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate

*Maximum temperature limited to 50C