



STERIDIUM

Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series	Plant growth chambers LED Lighting Temperature and Humidity
Model	pledt-rh-170

170 litre LED plant growth chamber
Temperature and humidity control



*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Plant growth chambers
LED Lighting
Temperature and Humidity
Model plect-rh-170

170 litre LED plant growth chamber
Temperature and humidity control

Chamber capacity	170 Litres
Chamber width	700 mm
Chamber depth	600 mm
Chamber height	405 mm
Chamber material	Stainless Steel 304L
External width	866 mm
External depth	784 mm
External height	1085 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	4 to 50C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Shelves supplied	1
Shelf dimensions	690 x 590 mm
Shelf spacing	84 mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm
Compressor size	1/3 HP
Refrigerant	CFC-Free R134a
Lighting source	Waterproof LED - lighting directly above entire shelf Mounted in lighting cassettes - height adjustable
Growth height	90 - 270mm height from shelf to light source
Growth area	0.4m ² (1 shelf)
Maximum intensity	150µmol/m ² /sec



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet


Series Plant growth chambers
LED Lighting
Temperature and Humidity
Model pledt-rh-170

170 litre LED plant growth chamber
Temperature and humidity control

Lighting colours

Lighting cassettes comprised of any combination of:

Warm White
Cool White
Red
Green
Blue
RGB Combination—Variable spectrum



Electrical supply

Single phase, 220 - 240V, 50 - 60 Hz
(alternatives available on request)

Element rating

0.75 kW

Circulating fan

1

Controller type

Multifunction intelligent digital PID-microprocessor

Readout

Digital LCD readout of set and actual temperature

Temperature alarms

High | low | deviation

Programmable control

500 step programmable control of temperature, humidity
and lighting

Country of origin

Australia




Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Plant growth chambers
LED Lighting
Temperature and Humidity
Model pledt-rh-170

170 litre LED plant growth chamber
Temperature and humidity control

Humidity Range	20 - 90% RH
Humidity sensor	
Control accuracy	0.1 %
Temporal stability	0.5 %



If the temperature setpoint is below 20 or above 80C, the RH control will be disabled and the chamber will adopt a natural value depending on the internal chamber conditions

This graph is a guide only
Variations to the envelope can occur due to ambient conditions,
the intensity of internal lighting, heat loads or humidity loads,
and the nature of the product placed within the chamber.



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series	Plant growth chambers LED Lighting Temperature and Humidity
Model	pledtrh-170

170 litre LED plant growth chamber
Temperature and humidity control

Options / Accessories

- Additional shelves
- 8 Step programmable controller
- 500 Step programmable controller
- Inner viewing door - toughened glass
- Double glazed glass door
- Side access port - 50 mm
- Fan speed controller
- Internal power supply*
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Co2 Control (ambient to 3000ppm)

*Maximum temperature limited to 50C