



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series	Seed germination chambers LED Lighting Temperature and Humidity
Model	sgledt-rh-1620

1620 litre seed germination chamber
LED lighting
Temperature and humidity control



*Specifications subject to change without notice

Steridium Pty Ltd | Australia
www.steridium.com
sales@steridium.com
+61 7 55 931 352



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Seed germination chambers
LED Lighting
Temperature and Humidity
Model sgledt-rh-1620

1620 litre seed germination chamber
LED lighting
Temperature and humidity control

Chamber capacity	1620 Litres
Standard dual chamber design	1 set of shelves per door
Chamber width	705 mm
Chamber depth	600 mm
Chamber height	1810 mm
Chamber material	Stainless Steel 304L
External width	1895 mm
External depth	762 mm
External height	2401 mm
External material	Durable epoxy powder-coated steel
Recommended clearance	75mm on sides and rear
Temperature range	4 to 50C
Temperature sensor	Pt100
Control accuracy	0.1 C
Temporal stability	0.2 C
Available shelf positions	38 (19 per door)
Shelves supplied	2 (1 per door)
Shelf dimensions	690 x 590 mm
Shelf spacing	90 mm
Shelf capacity	50 KG
Insulation type	Mineral Wool - asbestos free
Insulation thickness	50mm
Compressor size	3/4 HP
Refrigerant	CFC-Free R134a



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Seed germination chambers
LED Lighting
Temperature and Humidity
Model sgledt-rh-1620

1620 litre seed germination chamber
LED lighting
Temperature and humidity control

Lighting source	Waterproof LED - side mounted on each shelf position
Growth height	90mm
Growth area	1.6m ² (4 shelves)
Maximum intensity	1250 LUX (Infinitely adjustable)
Adjustability	Infinitely adjustable intensity
Lighting colours	Cool white Warm white Combination (Cool & Warm white)
Growth height	90 - 1710 mm - Adjustable
Growth area	15.46m ² (38 shelves)
Electrical supply	Single phase, 220 - 240V, 50 - 60 Hz (alternatives available on request)
Element rating	0.75 kW
Circulating fan	1
Controller type	Multifunction intelligent digital PID-microprocessor
Readout	Digital LCD readout of set and actual temperature
Temperature alarms	High low deviation
Diurnal Control	Automatic switching between selected Day and Night Temperatures (and lights)
Country of origin	Australia




Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series Seed germination chambers
LED Lighting
Temperature and Humidity
Model sgledt-rh-1620

1620 litre seed germination chamber
LED lighting
Temperature and humidity control

Humidity Range	20 - 90% RH
Humidity sensor	
Control accuracy	0.1 %
Temporal stability	0.5 %



If the temperature setpoint is below 20 or above 80C, the RH control will be disabled and the chamber will adopt a natural value depending on the internal chamber conditions

This graph is a guide only
Variations to the envelope can occur due to ambient conditions,
the intensity of internal lighting, heat loads or humidity loads,
and the nature of the product placed within the chamber.



Australia's premium manufacturer
of medical and laboratory products

Product Specification Sheet

Series	Seed germination chambers LED Lighting Temperature and Humidity
Model	sgledt-rh-1620

1620 litre seed germination chamber
LED lighting
Temperature and humidity control

Options / Accessories

- Single chamber design
- Additional shelves
- 8 Step programmable controller
- 500 Step programmable controller
- Inner viewing door - toughened glass
- Double glazed glass door
- Side access port - 50 mm
- Fan speed controller
- Internal power supply*
- Inner viewing light - LED*
- RS232 or RS485 comms module
- Ethernet comms module
- ISPM 15 compliant crating for export
- Calibration certificate
- Additional lighting (LED)
 - Red
 - Blue
 - Green
 - RGB Combination
- Co2 Control (ambient to 3000ppm)